

**Product Data Sheet**

**Application:** Internal Walls and Floors

# ACOUSTIC PARTITION ROLL (APR 1200)



## Acoustic Insulation for Internal Stud Walls and Floors

Acoustic Partition Roll (APR 1200) is a glass mineral wool roll that can provide high levels of acoustic performance in metal and timber internal stud walls as well as timber joist separating and internal floors. To support ease of installation, it is supplied in 600mm widths for an easy friction fit between stud centres.

## Features and Benefits



### Excellent Acoustic Performance

Delivers a measurable reduction in sound transmission through a wide variety of internal stud walls and floors.



### Easy to Install

Straightforward to handle, cut and install with minimal waste (off-cuts can be reused). Friction fits between 600mm stud centres with no need for additional fixings.



### Fire Classification

Achieves a Euroclass A1 Reaction to Fire classification, according to EN 13501-1.



### Sustainability

Achieves a BRE Green Guide rating of A+ which can assist in demonstrating environmental performance in your BREEAM assessments. Manufactured from up to 75% recycled glass on a plant that uses 100% renewable electricity. For further details, see the Environmental section below or visit [insulation-uk.com/CSR](http://insulation-uk.com/CSR)



### British Gypsum SpecSure® Warranty

Features in a number of British Gypsum proprietary systems - for more details, visit [british-gypsum.com/literature/white-book](http://british-gypsum.com/literature/white-book). The SpecSure® warranty confirms British Gypsum proprietary systems will perform as specified for the lifetime of the building. For further details, please visit [british-gypsum.com/technical-advice/specsure](http://british-gypsum.com/technical-advice/specsure)

# Key Considerations

When using ISOVER Acoustic Partition Roll (APR 1200), you need to satisfy yourself that use of the product meets all relevant national Building Regulations and guidance as well as local, national and other applicable standards relevant for your construction or application, including requirements in relation to fire and applicable height restrictions.

Please refer to the following product documents:

- Declaration of Performance - available at [insulation-uk.com/products/isover-acoustic-partition-roll-apr-1200](https://insulation-uk.com/products/isover-acoustic-partition-roll-apr-1200)
- Safe Use Instruction Sheet - available at [insulation-uk.com/healthandsafety](https://insulation-uk.com/healthandsafety)

# Product Specification

Product code	Thickness (mm)	Length (m)	Width (m)	Roll area (m <sup>2</sup> )	Rolls per pallet	Pallet area (m <sup>2</sup> )
5200625577	25	20.00	2 x 0.60	24.00	24	576.00
5200625578	50	13.00	2 x 0.60	15.60	24	374.40
5200625579	65	10.00	2 x 0.60	12.00	24	288.00
5200625580	75	12.20	2 x 0.60	14.64	24	351.36
5200625581	100	9.17	2 x 0.60	11.00	24	264.10

# Characteristics

<b>Fire</b>	Euroclass A1 Reaction to Fire classification according to EN 13501-1.	<b>Certification</b>	UKCA Marked to BS EN 13162. CE marked to EN 13162. Designation code: MW-EN 13162-T1.
<b>Environmental</b>	All ISOVER products are manufactured under Environmental Management System – ISO 14001:2015. BES 6001 Rating “Good” - The Framework Standard for Responsible Sourcing. Please visit <a href="https://insulation-uk.com/">insulation-uk.com/</a> accreditations for further details. Achieves an A+ Green Guide rating for glass mineral wool insulation (ref 815320002 for 25-65mm thickness, ref 815320005 for 75-100mm thickness) that can assist in demonstrating the environmental performance within BREEAM assessments.	<b>Handling, Storage, Health and Safety</b>	Information regarding storage, installation and handling of ISOVER products and health & safety information can be found at <a href="https://insulation-uk.com/healthandsafety">insulation-uk.com/healthandsafety</a> . Achieves a Eurofins Gold product status for indoor air quality (certificate available at <a href="https://insulation-uk.com/Eurofins">insulation-uk.com/Eurofins</a> ). EUCEB certified, demonstrating our mineral wool fibre products conform with Note Q of Regulation (EC) No 1272/2008 (to download the certification, please visit <a href="https://insulation-uk.com/accreditations">insulation-uk.com/accreditations</a> ).
<b>Recycled Content</b>	Manufactured from up to 75% recycled glass.	<b>Quality</b>	All ISOVER products are manufactured under Quality Management Standard – ISO 9001.



**ISOVER**

White House Industrial Estate,  
Runcorn, Cheshire, WA7 3DP

**Customer Service -  
Order Placement and Enquiries**

Tel: 01473 820820

Email: [iukcustomerservice@saint-gobain.com](mailto:iukcustomerservice@saint-gobain.com)

**Technical Support Centre**

Tel: 01473 820850

Email: [technicalsupport@saint-gobain.com](mailto:technicalsupport@saint-gobain.com)

**[insulation-uk.com](http://insulation-uk.com)**

Published date: 08 Feb 2023

Document reference: 001-448

ISOVER reserves the right to amend or revise product specification without notice. The information in this publication is correct at the time of publication. The information herein should not be read in isolation as it is meant only as guidance for the user, who should always ensure that they are fully conversant with the products and systems being used and their subsequent installation prior to the commencement of work.

For an up-to-date library of product information, users should visit the website at [insulation-uk.com](http://insulation-uk.com)

Saint-Gobain ISOVER UK Registered in England. Company Number 10442670.

Registered Offices: Saint-Gobain House, East Leake, Loughborough, Leicestershire, LE12 6JU.